



- Two-Way Rewind
- Auto-Sync Rewind
- Speed Regulation Rewind
- Rewind/Unwind

Model	bsc-A6	bsc-A8	bsc-A9
Rewind Speed	1-12 inch/s	1-12 inch/s	1-15 inch/s
Max. label Width	120 mm	180mm	230mm
Label Roll Diameter	Max.O.D.230mm		Max.O.D.360mm
Core Diameter	1"(25mm)/1.5"(40mm)/3"(76mm)		
Rewinding Type	Auto-Sync Rewind、Two-way Rewind、 speed regulating rewinding, Rewind/Unrewind		
Induction Method	Rod Induction		
Power	Input:100-240V 50/60Hz DC Output:24V		
Dimension	(L)276mm*(W)230mm*(H)260mm	(L)336mm*(W)230mm*(H)278mm	(L)453mm*(W)360mm*(H)420mm
Carton size	(L)325mm*(W)275mm*(H)335mm	(L)400mm*(W)295mm*(H)345mm	(L)510mm*(W)340mm*(H)425mm
Net weight	4KG	5.5KG	14KG
Gross weight	5KG	6.8KG	15KG
Environment	Temperature: 0-45°C Relative humidity: 25%-85%		
Certification	CE 、 FCC 、 RoHs		
Label rewinding type	Paper/cloth/film: copperplate paper adhesive, synthetic paper, thermal paper, washing cloth/shipping mark, card/hanging tag, PET/PVC/PP,Bar code label, supervision code label, security label, all kinds of flexible film packaging material		