



## DA210/DA220 SERIES – Desktop Direct Thermal Bar Code Printer

### COMPACT DESIGN

### AFFORDABLE TOTAL COST OF OWNERSHIP



#### KEY FEATURES

- ▣ High quality double-walled clamshell design
- ▣ 6 inches per second print speed
- ▣ 64 MB DRAM and 128 MB Flash memory (DA220/DA320)
- ▣ Easy media loading
- ▣ USB 2.0 (High speed mode)
- ▣ Versatile TSPL-EZD firmware emulates Eltron®, Zebra® and Datamax languages out of the box
- ▣ Bluetooth 4.0
- ▣ 802.11 a/b/g/n (DA220/DA320)
- ▣ ENERGY STAR® qualified
- ▣ Linerless solution

#### APPLICATIONS

- ▣ Small Parcel Shipping
- ▣ Mail Room Address and Routing Labels
- ▣ Shipping & Receiving
- ▣ Entertainment and Transportation Ticketing
- ▣ Retail Point-of-Sale
- ▣ File-Folder Labeling

## DA210/DA220 SERIES – Desktop Direct Thermal Bar Code Printer

| PRINTER MODEL                 | DA210                                                                                                                                                                                                                                                                                                                                                                                      | DA310                          | DA220                                                                                                                                                                                                                                                                                       | DA320                            |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| Resolution                    | 8 dots/mm (203 DPI)                                                                                                                                                                                                                                                                                                                                                                        | 12 dots/mm (300 DPI)           | 8 dots/mm (203 DPI)                                                                                                                                                                                                                                                                         | 12 dots/mm (300 DPI)             |
| Printing method               | Direct Thermal                                                                                                                                                                                                                                                                                                                                                                             |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Max. print speed              | 152.4 mm (6")/second                                                                                                                                                                                                                                                                                                                                                                       | 102 mm (4")/second             | 152.4 mm (6")/second                                                                                                                                                                                                                                                                        | 102 mm (4")/second               |
| Max. print width              | 108 mm (4.25")                                                                                                                                                                                                                                                                                                                                                                             | 105.7 mm (4.16")               | 108 mm (4.25")                                                                                                                                                                                                                                                                              | 105.7 mm (4.16")                 |
| Max. print length             | 2,794 mm (110")                                                                                                                                                                                                                                                                                                                                                                            | 1,016 mm (40")                 | 25,400 mm (1000")                                                                                                                                                                                                                                                                           | 11,430 mm (450")                 |
| Enclosure                     | Double-walled plastic                                                                                                                                                                                                                                                                                                                                                                      |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Physical dimension            | 172 mm (W) x 165 mm (H) x 195 mm (D)<br>6.77" (W) x 6.50" (H) x 7.68" (D)                                                                                                                                                                                                                                                                                                                  |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Weight                        | 1.5 kg (3.31 lbs)                                                                                                                                                                                                                                                                                                                                                                          |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Label roll capacity           | 127 mm (5") OD                                                                                                                                                                                                                                                                                                                                                                             |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Processor                     | 32-bit RISC CPU                                                                                                                                                                                                                                                                                                                                                                            |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Memory                        | <ul style="list-style-type: none"><li>• 8 MB Flash memory</li><li>• 16 MB DRAM</li></ul>                                                                                                                                                                                                                                                                                                   |                                | <ul style="list-style-type: none"><li>• 128 MB Flash memory</li><li>• 64 MB DRAM</li></ul>                                                                                                                                                                                                  |                                  |
| Interface                     | <ul style="list-style-type: none"><li>• USB 2.0 (High speed mode)</li><li>• Internal Bluetooth (factory option)</li></ul>                                                                                                                                                                                                                                                                  |                                | <ul style="list-style-type: none"><li>• PCBA1: USB 2.0 high speed mode, USB Host, RS-232 and Ethernet (standard)</li><li>• PCBA2: USB 2.0 and Ethernet (factory option)</li><li>• Internal 802.11 a/b/g/n wireless (factory option)</li><li>• Internal Bluetooth (factory option)</li></ul> |                                  |
| Power                         | External universal switching power supply <ul style="list-style-type: none"><li>• Input: AC 100-240V, 50-60Hz</li><li>• Output: DC 24V, 2.5A, 60W</li></ul>                                                                                                                                                                                                                                |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Operation switch, button, LED | 1 power switch, 1 feed button & 1 LED (3 colors: green, amber & red)                                                                                                                                                                                                                                                                                                                       |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Sensors                       | <ul style="list-style-type: none"><li>• Transmissive gap sensor</li><li>• Black mark reflective sensor</li><li>• Head open sensor</li></ul>                                                                                                                                                                                                                                                |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Internal fonts                | <ul style="list-style-type: none"><li>• 8 alpha-numeric bitmap fonts</li><li>• Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font</li></ul>                                                                                                                                                                                                        |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Bar code                      | <ul style="list-style-type: none"><li>• 1D bar code</li><li>Code 39, Code 93, Code128UCC, Code128 subsets A.B.C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11, China Post</li><li>• 2D bar code</li><li>PDF-417, Maxicode, DataMatrix, QR code, Aztec, MicroPDF417</li></ul> |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Font and barcode rotation     | 0, 90, 180, 270 degree                                                                                                                                                                                                                                                                                                                                                                     |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Printer language              | TSPLE-EZD (Compatible to EPL, ZPL, ZPL II, DPL)                                                                                                                                                                                                                                                                                                                                            |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Media type                    | Continuous, black mark, fan-fold, notched (outside wound)                                                                                                                                                                                                                                                                                                                                  |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Media width                   | 19 ~ 114 mm (0.7" ~ 4.5")                                                                                                                                                                                                                                                                                                                                                                  |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Media thickness               | 0.055 ~ 0.19 mm (2.16 ~ 7.48 mil)                                                                                                                                                                                                                                                                                                                                                          |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Media core diameter           | 25.4 ~ 38 mm (1" ~ 1.5")                                                                                                                                                                                                                                                                                                                                                                   |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Label length                  | 10 ~ 2,794 mm<br>(0.39" ~ 110")                                                                                                                                                                                                                                                                                                                                                            | 10 ~ 1,016 mm<br>(0.39" ~ 40") | 10 ~ 25,400 mm<br>(0.39" ~ 1000")                                                                                                                                                                                                                                                           | 10 ~ 11,430 mm<br>(0.39" ~ 450") |
| Environment condition         | Operation: 5 ~ 40°C, 25 ~ 85% non-condensing<br>Storage: -40 ~ 60°C, 10 ~ 90% non-condensing                                                                                                                                                                                                                                                                                               |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Safety regulation             | FCC Class A, CE Class A, RCM, CB, CCC, ENERGY STAR®, KC, BIS, UL, EAC                                                                                                                                                                                                                                                                                                                      |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Environmental concern         | Comply with RoHS, WEEE                                                                                                                                                                                                                                                                                                                                                                     |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Accessories                   | <ul style="list-style-type: none"><li>• Windows labeling software CD disk</li><li>• Quick start guide</li><li>• USB cable</li><li>• Power cord</li><li>• External universal switching power supply</li></ul>                                                                                                                                                                               |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Limited warranty              | <ul style="list-style-type: none"><li>• Printer: 2 years</li><li>• Print head: 25 km (1 million inches) or 12 months which comes first</li><li>• Platen: 50 km (2 million inches) or 12 months which comes first</li></ul>                                                                                                                                                                 |                                |                                                                                                                                                                                                                                                                                             |                                  |
| Factory options               | <ul style="list-style-type: none"><li>• Internal Bluetooth</li></ul>                                                                                                                                                                                                                                                                                                                       |                                | <ul style="list-style-type: none"><li>• Real Time Clock</li><li>• Internal 802.11 a/b/g/n wireless</li><li>• Internal Bluetooth</li><li>• PCBA2: USB2.0 and Ethernet</li></ul>                                                                                                              |                                  |
| Dealer options                | N/A                                                                                                                                                                                                                                                                                                                                                                                        |                                | <ul style="list-style-type: none"><li>• Peel-off module</li><li>• Guillotine cutter (full cut or partial cut)</li><li>• Linerless with cutter</li><li>• Linerless with tear</li></ul>                                                                                                       |                                  |
| User options                  | <ul style="list-style-type: none"><li>• 1.5" adaptor for 1.5" paper core</li><li>• External roll mount, media OD. 214 mm (8.4") with 76.2 mm (3") core</li></ul>                                                                                                                                                                                                                           |                                | <ul style="list-style-type: none"><li>• 1.5" adaptor for 1.5" paper core</li><li>• External roll mount, media OD. 214 mm (8.4") with 76.2 mm (3") core</li><li>• KP-200 Plus keyboard display unit (serial interface)</li></ul>                                                             |                                  |



### CORPORATE HEADQUARTERS

TSC Auto ID Technology Co., Ltd.  
Tel: +886 2 2218 6789  
E-mail: [apac\\_sales@tscprinters.com](mailto:apac_sales@tscprinters.com)

### LI ZE PLANT

TSC Auto ID Technology Co., Ltd.  
Tel: +886 3 990 6677  
E-mail: [apac\\_sales@tscprinters.com](mailto:apac_sales@tscprinters.com)

### AMERICAS

TSC Auto ID Technology America Inc.  
Tel: +1 657 258 0808  
E-mail: [americas\\_sales@tscprinters.com](mailto:americas_sales@tscprinters.com)

### MEXICO

TSC Mexico Representative Office  
Tel: +1 52 (33) 3673 1406  
E-mail: [americas\\_sales@tscprinters.com](mailto:americas_sales@tscprinters.com)

### BRAZIL

TSC Brazil Representative Office  
Tel: +55 (11) 3554 7225  
E-mail: [americas\\_sales@tscprinters.com](mailto:americas_sales@tscprinters.com)

### EMEA

TSC Auto ID Technology EMEA GmbH  
Tel: +49 (0) 8106 37979 000  
E-mail: [emea\\_sales@tscprinters.com](mailto:emea_sales@tscprinters.com)

### RUSSIA

TSC Auto ID Technology EMEA GmbH  
Tel: +7 495 646 3538  
E-mail: [emea\\_sales@tscprinters.com](mailto:emea_sales@tscprinters.com)

### Middle East

TSC Auto ID Technology ME Ltd, FZE  
Tel: +971 4 2533 069  
E-mail: [emea\\_sales@tscprinters.com](mailto:emea_sales@tscprinters.com)

### ASIA PACIFIC

TSC Auto ID Technology Co., Ltd.  
Tel: +886 2 2218 6789  
E-mail: [apac\\_sales@tscprinters.com](mailto:apac_sales@tscprinters.com)

### INDIA

TSC India Distributor's Office  
Tel: +91 2249 679 315  
E-mail: [apac\\_sales@tscprinters.com](mailto:apac_sales@tscprinters.com)

### CHINA

Tianjin TSC Auto ID Technology Co., Ltd.  
Tel: +86 22 5981 6661  
E-mail: [apac\\_sales@tscprinters.com](mailto:apac_sales@tscprinters.com)

### KOREA

TSC Korea Representative Office  
Tel: +82 2 852 3322  
E-mail: [apac\\_sales@tscprinters.com](mailto:apac_sales@tscprinters.com)